

# AEROSOUND®

🌐 [www.aerofoam.ae](http://www.aerofoam.ae)




# INDEX

<b>Introduction</b>	<b>3-4</b>
<b>AeroSound® Duct Liners &amp; Sound Absorbers</b>	<b>5-8</b>
<b>AeroSound® Sound Lagging Material &amp; Barriers</b>	<b>9-14</b>
<b>AeroSound® Floor Underlays</b>	<b>15-19</b>
<b>AeroSound® Gym Flooring</b>	<b>20-23</b>


## DID YOU KNOW?

International building codes indicate minimum requirements for design, construction and operations of buildings. That includes acoustic comfort of building's end users. Each country may follow their own standards for maximum allowable noise level in residential buildings, hotels, schools, etc.



# Annoyed by the loud noises in your building?

## It's time to take noise pollution seriously!




Noise pollution can have adverse effects on all of us. Constant exposure to loud noise or impact sound can cause increased tiredness, lack of concentration, disturbed sleep and compromised acoustic comfort of building users. Sound reduction solutions should be considered during design and construction stage to assure the highest performance.

**AeroSound® Acoustic Solutions** are designed to absorb or block the unwanted sound in your building. Properly selected material can control impact noise or airborne sound depending on the application, which as a result provides necessary acoustic comfort for the residents of the building.

AEROSOUND®

# Duct Liners & Sound Absorbers




**Acoustic absorbers and duct liners are designed especially to absorb unwanted airborne sound from multiple sources.**



## Acoustic Duct Liners & Sound Absorbers

AeroSound® Duct Liners are a wide range of sound absorbers developed to reduce noise in different applications. Advanced technologies utilized during the manufacturing of AeroSound® Duct Liners assure high quality of materials which are durable, easy to install, safe, hygienic and odor free.




### AeroSound® LX

Polyolefin based  
Semi open cell  
With or without self-adhesive  
\*Applicable for 25 mm.

NRC = 0.35\*

$\alpha = 0.30^*$




### AeroSound® LXF

Polyolefin based  
Aluminum foil facer  
Semi open cell  
With or without self-adhesive  
\*Applicable for 25 mm.

NRC = 0.45\*

$\alpha = 0.40^*$




### AeroSound® LN

Elastomeric based  
Semi open cell  
With or without self-adhesive  
\*Applicable for 25 mm.

NRC = 0.45\*

$\alpha = 0.40^*$



### AeroSound® ESA

Elastomeric based  
Open cell  
With or without self-adhesive  
\*Applicable for 50 mm.

NRC = 0.85\*

$\alpha = 0.85^*$

## FEATURES

-  Excellent sound absorption
-  Dust and fiber free
-  Does not absorb unwanted odors
-  Hygienic & easy to clean
-  Safe to handle
-  Easy to install
-  Resistant to water & cleaning detergents
-  Resistant to bacteria
-  Resistant to mold and mildew
-  Excellent thermal properties
-  Lightweight
-  Long technical life
-  Environment friendly

## APPLICATIONS

-  Duct liners
-  Wall partitions
-  Decorative acoustic panels
-  Machinery casing
-  Operating cabins
-  Silencers
-  Decompression Plenum boxes

## ACCESSORIES

Accessories are available with or without self-adhesive layer. Additional accessories are not required. For easy installation, remove the release liner and glue the material to the surface. Refer to AeroSound® Installation Manual for more information.

# TECHNICAL PROPERTIES

	AeroSound® LX XLPE Plain			AeroSound® LXF XLPE with foil			AeroSound® LN Elastomeric			AeroSound® ESA Elastomeric															
Properties	Value/Assessment												Tested acc. to:												
Acoustic	Thickness	NRC	$\alpha_w$	Thickness	NRC	$\alpha_w$	Thickness	NRC	$\alpha_w$	Thickness	NRC	$\alpha_w$	ISO 354												
	15 mm	0.35	0.20	15 mm	0.25	0.20	13 mm	0.35	0.30	10 mm	0.35	0.25													
	25 mm	0.35	0.30	25 mm	0.45	0.40	15 mm	0.45	0.40	15 mm	0.55	0.35													
							25 mm	0.45	0.45	25 mm	0.70	0.50													
										50 mm	0.85	0.85													
Other	Density of foam	30 kg/m <sup>3</sup> ( $\pm 10\%$ tol.)		30 kg/m <sup>3</sup> ( $\pm 10\%$ tol.)		60 kg/m <sup>3</sup> ( $\pm 10\%$ tol.)		ESA 160 - above 120 kg/m <sup>3</sup> ESA 240 - 220 to 260 kg/m <sup>3</sup>		ASTM C518															
	Thermal Conductivity	0.036 W/m•K at 23 °C		0.036 W/m•K at 23 °C		0.033 W/m•K at 23 °C		0.041 W/m•K at 23 °C		BS 476 Part 6 & 7															
	Reaction to fire			Class 0				Class 1		ASTM E84															
	VOC level	<0.5 mg.m <sup>3</sup>		<0.5 mg.m <sup>3</sup>						ASTM D5116															
	Water absorption	2.03% - 2.7%		2.03% - 2.7%		0.28% - 0.99%				ASTM D570															
	Max. operating temp.	105 °C, +85 °C (adhesive)		105 °C, +85 °C (adhesive)		110 °C, +85 °C (adhesive)		105 °C, +85 °C (adhesive)		ASTM C411															
	Max. air velocity	25.4 m/s (5000 fpm)												Internal test											
	Antifungal	Yes												ASTM G21											
	Color	Gray		Blue-Gray		Black		Black-Gray		1 m x 1 m ( $\pm 20$ mm tolerance)															
Physical	Available size	12 mm - 1.2 m x 20 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		12 mm - 1.2 m x 20 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		13 mm - 1 m x 12 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)																			
		15 mm - 1.2 m x 20 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		15 mm - 1.2 m x 20 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		15 mm - 1 m x 12 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)																			
		20 mm - 1.2 m x 20 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		20 mm - 1.2 m x 20 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		19 mm - 1 m x 10 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)																			
		25 mm - 1.2 m x 2.4 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		25 mm - 1.2 m x 2.4 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)		25 mm - 1 m x 8 m (W: $\pm 20$ mm; L: $\pm 50$ mm tolerance)																			
Thickness										6, 10, 15, 20, 25, 30, 40, 50 mm															

## EXAMPLE OF APPLICATIONS


AeroSound® Duct Liners are easy to install and do not require use of any additional accessories as they are supplied a self adhesive layer. Additionally, they pose no harm to installers as they are free of fiber and dust.

1. Cut the sheets into the desired size and shape
2. Remove the release liner
3. Glue the material to the surface

Refer to AeroSound® Installation Manual for more information.



Scan the QR code  
to view the installation  
manual.



### How to calculate the final noise output?

AeroSound® Acoustic Software can be used to calculate the final approximate noise level from ventilation and air conditioning duct systems while using selected thickness of AeroSound® Duct Liners.

Visit our website: [www.aerofoam.ae](http://www.aerofoam.ae)

Scan the QR code  
to download the  
desktop app.



## OTHER EXAMPLES OF APPLICATIONS

**Generators**



**Air Handling Units**



**Engine Compartments**



**Special Utility Vehicle**



AEROSOUND®

# Acoustic Panels




Acoustic panels can be highly effective solutions at solving acoustic issues that can be observed in offices, schools, auditoriums, restaurants, hotels, meeting rooms, or any other place where large amount of people are situated.

AeroSound® Acoustic Panels are not only great sound absorbers that can be placed on the walls or ceilings, but can also be considered as personalized décor in your surroundings!

The solutions can be customized to a variety of sizes, colors, shapes and designs! Moreover, it they can be part of interior design and can be custom manufactured as per the designers concept.

AEROSOUND®

# Sound Lagging Material & Barriers



**Sound lagging materials and sound barriers help block unwanted sound and noise from wastewater and drain pipes but also create walls, ceilings, or enclosures that are soundproof for noisy equipment.**


## Sound Lagging Material & Sound Barriers

AeroSound® Sound Lagging Materials are designed to reduce sound propagation coming from various sources. They have been designed for covering wastewater or drainage pipes, but act as an excellent sound barrier that can be installed as an additional layer for wall partitions.



### AeroSound® SLM

Convoluted PU foam  
Bonded to flexible MLV (mass loaded vinyl) acoustic barrier  
With pure aluminum foil facer  
Available with glasswool (AeroSound® SLM/GW)



### AeroSound® SL+

Semi open cell elastomeric foam  
Bonded to solid high mass rubber



## FEATURES

- Excellent acoustic properties
- Dust & fiber free
- Safe to handle
- Easy to install
- Hygienic & easy to clean
- Excellent thermal properties
- Long technical life
- Environment friendly


## APPLICATIONS

- Wastewater pipes
- Garbage chutes
- Engine compartments
- Air ducts (outer surface)
- Wall partitions
- Ventilation fans coverings
- Compressor units' coverings
- Machinery castings

## ACCESSORIES

Tapes & Adhesive

Templates



Refer to AeroSound® Installation Manual for more information.


# TECHNICAL PROPERTIES

	AeroSound® SLM	AeroSound® SL+		
<b>Properties</b>	<b>Value/Assessment</b>		<b>Tested acc. to:</b>	
Acoustic	Sound Transmission Class (STC) Sound Reduction Index $R_w$ Wastewater Sound Reduction Operating temperature Thermal conductivity	30 dB (C;Ctr) = 30 dB (-1; -4) dB 12 dB to 17 dB -40 °C to +100 °C 0.042 W/m•K at 23 °C	30 dB (C;Ctr) = 30 dB (-1; -4) dB 12 dB to 17 dB -40 °C to +100 °C	ASTM E90 ASTM E413 EN ISO 10140-2 EN ISO 14366 ASTM C518 ASTM E84 BS 476 Part 6 & 7 AS 1530.3
Other	Reaction to fire	FSI<25, SDI<50 Class 0 Ignitability - 0 Flame propagation - 0 Heat release - 0 Smoke developed index - 1	Class 0	ASTM D5116
Physical	TVOC - Emission rate CFC, HCFC, dust, fibers & asbestos	<0.5 mg/m <sup>2</sup> /hr Free	Free	
	Color	Foam - orange Barrier - silver	Foam - black Barrier - black	
	Size	W: 1350 mm (±20 mm) L: 2.5 m & 5 M (±50 mm)	1 m x 1 m or 1 m x 2 m (W: ±20 mm, L: ±50 mm)	
	Thickness	25 mm (±5 mm)	8, 13, 20, 25 mm (±1,5 mm)	
	Weight	4.5 ÷ 5 kg/m <sup>2</sup>	From 5.27 kg/m <sup>2</sup> to 6.3 kg/m <sup>2</sup> <small>(depending on thickness)</small>	
	Customized Weight	2.5 kg/m <sup>2</sup> , 3 kg/m <sup>2</sup> , 6 kg/m <sup>2</sup> , 8 kg/m <sup>2</sup> *		
	Density		Density of foam: 45-65 kg/m <sup>3</sup> Density of solid rubber: 1560-2000 kg/m <sup>3</sup>	depending on thickness

\*Customized product weight upon request, thickness of the MLV barrier will be adjusted accordingly (1.2 mm ÷ 5 mm).

## EXAMPLE OF APPLICATIONS

### 1. Wastewater pipe




1. Cut the sheets into the desired size and shape and apply it over the surface.
2. Use tape to cover the joints.

Refer to AeroSound® Installation Manual for more information.



Scan to watch installation video

### 2. Wall partitions



1. Apply the material over the metal frame




Scan the QR code to view the installation manual.



# AEROSOUND®


## Acoustic Barriers

AeroSound® Acoustic Barriers are designed to reduce sound transmission. It can be installed by itself or along with other AeroSound® products. Especially recommended for industrial/automotive applications and machinery where high mechanical strength of material is expected.




**AeroSound® HD**

Solid flexible rubber




**AeroSound® HDM**

Flexible MLV  
(Mass Loaded Vinyl)



**AeroSound® ALM**

Flexible MLV  
(Mass Loaded Vinyl)  
With aluminum foil facing



**AeroSound® RFM**

Flexible MLV  
(Mass Loaded Vinyl)  
Reinforced with non-woven  
fiber glass cloth

## FEATURES

-  Excellent acoustic properties
-  Dust & fiber free
-  Safe to handle
-  Easy to install
-  Flexible
-  Hygienic & easy to clean
-  Resistant to chemicals
-  Long technical life
-  Environment friendly

Properties	AeroSound® HD	AeroSound® HDM	AeroSound® ALM	AeroSound® RFM
Thickness	3 mm	4 mm	2-4 mm	2-4 mm
Size	1 m x 1 m 1 m x 2 m	1350 mm x 3 m 1350 mm x 5 m	1350 mm x 2.5 m 1350 mm x 5 m	1350 mm x 2.5 m 1350 mm x 5 m
Weight	4.5-5 kg/m <sup>2</sup>	7.5-8 kg/m <sup>2</sup>	5 kg/m <sup>2</sup>	5 kg/m <sup>2</sup>

## ACCESSORIES

### Tapes & Adhesive



Refer to AeroSound® Installation Manual for more information.

# EXAMPLES OF APPLICATIONS

**Wastewater Pipe**




**Engine Compartments**

**Machinery Case**



## APPLICATIONS


- Wastewater pipes
- Garbage chutes
- Engine compartments
- Air ducts (outer surface)
- Wall partitions
- Ventilation fans coverings
- Compressor units' coverings
- Machinery castings



**Ventilation Fan Covering**

AEROSOUND®


# Acoustic Floor Underlay



**Floor Underlay are designed to reduce impact sound transmission in flooring systems.**

## Acoustic Floor Underlay

AeroSound® Floor Underlay are designed to reduce impact noise transfer within the building structure to avoid propagation of structural sound while using a combination of AeroSound® Underlay and AeroSound® Perimetric Tapes.



### AeroSound® RSF

Elastomeric rubber mat  
with recycled rubber content



### AeroSound® SF

Cross-linked  
Closed cell  
Polyolefin foam



### AeroSound® ESF

Closed cell  
Elastomeric foam

## FEATURES

-  Long lifespan
-  Environment friendly
-  Does not absorb water
-  Excellent acoustic properties
-  Helps to protect screed from cracking
-  Resistant to bacteria, mold & fungi growth

## APPLICATIONS

-  Gyms, clubs & dancing floors
-  Hotels, offices & medical facilities
-  Recording studios & movie theaters
-  Industrial buildings & machinery foundation
-  Automotive industry - wheel arch & chassis
-  Residential, commercial & high-rise buildings
-  Sports court & running track



# TECHNICAL PROPERTIES

	AeroSound® SF	AeroSound® ESF	AeroSound® RSF	Tested acc. to:
<b>Properties</b>	<b>Value/Assessment</b>			
Material type	Cross-linked polyolefin foam	Flexible elastomeric foam	Elastomeric rubber mat with recycled rubber content	
Color	Blue	Black	Black/Anthracite/Orange	
Thicknesses*	3, 5, 8, 10 mm	3, 5, 8, 10, 13 mm	2-12 mm	
Thickness tolerance	-1 mm / +1.5 mm		2-6 mm: ±0.3 mm 7-12 mm: ±0.5 mm	
Size	W: 1.2 m   L: 20 m	W: 1 m   L: 8-30 m	W: 1.2 m   L: 5-10 m	
Size tolerance	W: ±20 mm   L: ±50 mm			
Recycled content	No	No	Yes	
Dynamic stiffness	64.3 MN/m <sup>3</sup> (3 mm)	59.27 MN/m <sup>3</sup> (10 mm)	73 MN/m <sup>3</sup> (3 mm)	
Maximum load	400 kg/m <sup>2</sup>	400 kg/m <sup>2</sup>	3000 kg/m <sup>2</sup>	
Tensil strength at peak load	0.82 kg/m <sup>2</sup>	2.71 kg/m <sup>2</sup>	3.48 kg/m <sup>2</sup>	ASTM D412/ ASTM D751
Elongation break	36.37%	128.87%	47.5%	ASTM D412/ ASTM D751
Compressibility	84%	94.06%	93.7%	ASTM D3575/ ASTM F3616
Hardness, Shore A	11-17	15-18	65-69	ASTM D2240
Temperature range	-80 °C to +105 °C	-80 °C to +110 °C	-30 °C to +85 °C	
Thermal Conductivity at 23 °C	0.035 W/m·K	0.033 W/m·K	0.106 W/m·K	ASTM C518
Water absorption	0.013 g/cm <sup>2</sup>	0.09 g/cm <sup>2</sup>	0.009 g/cm <sup>2</sup>	JIS K 6767
Chemical resistance	Yes			
Resistance to fungi	Pass			ASTM G21
Resistance to bacteria	Pass			ISO 22196
ODP, GDP	ODP=0, GDP <5			
VOC			≤160 µg/m <sup>2</sup> hr	ASTM D5116
Puncture testing			91.44 cm	ASTM F924
Rolling load			Pass (at 500 cycles)	EN 985

\*Other thicknesses available upon request.

## ACCESSORIES



### Tapes & Adhesive



Refer to AeroSound® Installation Manual for more information.

# EXAMPLES OF APPLICATIONS


AeroSound® Floor Underlay can be installed in many different configurations and applications. Usual application is to separate concrete slab from the screed or final finish. For more details, please refer to AeroSound® Floor Underlay Brochure and AeroSound® Installation Handbook.



Scan to watch  
installation video




Scan the QR code  
to view the installation  
manual.




## AeroSound® RSF


WITHOUT SCREED APPLICATIONS




Ceramic tiles  
Adhesive  
AeroSound® RSF (2-12 mm)  
Concrete slab



Vinyl plank  
Adhesive  
AeroSound® RSF (2-12 mm)  
Concrete slab




Marble tile  
Adhesive  
AeroSound® RSF (2-12 mm)  
Concrete slab




Wood panels / HDF / MDF  
Adhesive  
AeroSound® RSF (2-12 mm)  
Concrete slab

## AeroSound® SF, ESF & RSF


WITH SCREED APPLICATIONS



Ceramic tiles  
Adhesive  
Screeed  
AeroSound® SF, ESF, RSF (2-12 mm)  
Concrete slab





Vinyl plank  
Adhesive  
Screeed  
AeroSound® SF, ESF, RSF (2-12 mm)  
Concrete slab



Marble tiles  
Adhesive  
Screeed  
AeroSound® SF, ESF, RSF (2-12 mm)  
Concrete slab



Wood panels / HDF / MDF  
Adhesive  
Screeed  
AeroSound® SF, ESF, RSF (2-12 mm)  
Concrete slab



AEROSOUND®

# Gym Flooring



**AeroSound® Gym Flooring provide excellent shock absorption and reduce impact sound transmission between floors.**

## Gym Flooring


AeroSound® Gym Flooring is a high density rubber flooring for all types of gym and workout areas. Depending on the product, AeroSound® Gym Flooring is a suitable solution for both indoor and outdoor applications, wherever extreme wear and tear is expected.

It provides excellent shock absorption for all types of workout activities but also reduces impact and sound transmission between floors. Availability of several product versions as well as customization, it can make your gym area not only unique, but also safe for its users!

## FEATURES

-  High scuff resistance
-  Aesthetic finish
-  Easy to clean
-  High durability
-  Long technical life
-  Non toxic formula

## ADVANTAGES




## AEROSOUND® GYM FLOORING RECOMMENDATIONS

AeroSound® Gym Flooring Type	Area of application		Type of Workout/Activity Recommendations						
	Indoor	Outdoor	Fitness	Aerobics	Yoga / Pilates	Weightlifting	Functional Training	Playgrounds	
HIIT	+			+	+	+			
Dynamic Flakes	+						+	+	+
Dynamic Star	+						+	+	+
Dynamic+	+	+					+	+	+
HIIT Flakes Tiles	+	+					+	+	+
HIIT Flakes	+	+	+	+	+				
Puzzle	+	+					+	+	+

## TECHNICAL DETAILS

Property	Units	Tested acc.:	Indoor			Outdoor			
			Dynamic Star	Dynamic Flakes	HIIT	HIIT Flakes Tile	Dynamic+	Puzzle	HIIT Flakes
Density	kg/m³	-	1000	1000	1000	1400	1000	1100	1300
Hardness	Shore A	ASTM D2240	70 ±5	70 ±5	70 ±5	65 ±5	65 ±5	65 ±5	60 ±5
Tensile strength	kg/m²	ASTM D412	13	12	13.5	8	8	12	9
Elongation at break	%	ASTM D412	51	49	31	39	40	40	73
Tear strength	N/mm	ASTM D624	9	11.3	6.3	8.4	5	16.5	6.8
Heat resistant at 70 °C for 72 h	-	ASTM D573	Pass						
Change in hardness	Shore A	ASTM D2240	+5	+4	+4	+4	+5	+4	+4
Change in tensile strength	%	ASTM D412	-27.5	-25.5	-25	-27.6	-27.4	-25	-24.5
Change in elongation	%	ASTM D412	-35.7	-31.5	-33	-32.9	-35.7	-35	-31.7

# AeroSound® Gym Flooring SBR-based Ideal solution for indoor workout areas!




## AeroSound® Dynamic Star

Thickness: 5-60 mm  
Size: 1 m x 1 m, 0.5 m x 0.5 m  
Color: Black tile



## AeroSound® Dynamic Flakes

Thickness: 5-60 mm  
Size: 1 m x 1 m, 0.5 m x 0.5 m  
Color: Black tile with colored flakes




## AeroSound® HIIT

Thickness: 2-12 mm  
Size: 1.2 m x 1.6 m  
Color: Black roll with colored flakes

## APPLICATIONS



Training rooms



Fitness centers



Health clubs

Flake colors:



for AeroSound® Dynamic HIIT, Dynamic Flakes & HIIT



Scan the QR code  
to view the installation  
manual.


# AeroSound® Gym Flooring EPDM-based Ideal solution for indoor & outdoor workout areas!



## AeroSound® Dynamic+

**Thickness:** 10-60 mm  
**Size:** 1 m x 1 m, 0.5 m x 0.5 m  
**Color:** SBR black granules + 3-5 mm thick EPDM colored granules


### EPDM granule colors:



## AeroSound® HIIT Flakes Tiles

**Thickness:** 5-60 mm  
**Size:** 1 m x 1 m  
**Color:** Gray tiles with colored flakes


### Flakes colors:



## AeroSound® HIIT Flakes

**Thickness:** 2-12 mm  
**Size:** 1 m x 1 m  
**Color:** Rolls with colored flakes

### Flakes colors:



## AeroSound® Puzzle

**Thickness:** 5-60 mm  
**Size:** 1 m x 1 m, 0.5 m x 0.5 mm  
**Color:** EPDM colored granules

### EPDM granule colors:




## APPLICATIONS



Open parks



Outdoor playgrounds



Indoor sports facilities

# AEROSOUND®

## Global Footprint



**Disclaimer:** This information on Hira Industries products is presented to the best of our knowledge. All product data is based on average values and is for guidance only. As these products are subject to constant research and development, we reserve the right to update the contents without notice.

Manufactured by Hira Industries  
P.O. Box 50673, Dubai - UAE  
+971 4 884 8414

✉ [enquiry@rhira.com](mailto:enquiry@rhira.com)  
🌐 [www.aerofoam.ae](http://www.aerofoam.ae)  
🌐 [www.rhira.com](http://www.rhira.com)

 **Hira**